


**510nm 20mW SM Coaxial Fiber Coupled Laser Diode with SMF | Green LD Module**  
**505nm~510nm 20mW SM Pigtailed LD with Single Mode Fiber (SM Fiber)**  
**RWLP-510-020m-4**

510nm Pigtailed Diode Laser		20mW/SM Fiber	
PARAMETER	SYMBOL	VALUE	UNIT
Reverse Voltage	$V_r$	2.0	V
Operating Temperature	$T_{op}$	-10 ~ +60	°C
Storage Temperature	$T_{stg}$	-40 ~ +85	°C
Lead soldering temperature (10 sec.)	$T_{is}$	260	°C
<b>Features:</b> <ul style="list-style-type: none"> <li>510nm Green Diode Laser</li> <li>3um SM Fiber</li> <li>Coaxial or B82 Package</li> </ul>			
<b>Applications:</b> <ul style="list-style-type: none"> <li>Medical Laser Treatment</li> <li>Others</li> </ul>			
<b>Specifications</b>	<b>RWLP-510-020m-4</b>		
	Min	Type	Max
Center Wavelength@25°C	510nm±10nm		
Spectral Width (FWHM)	----	2.0nm	----
Output Power	----	20mW	----
Fiber Type	Single Mode Fiber		
Fiber Core	3um		
Recommend Operating Temperature	25°C		
Fiber Connector	FC/SC/SMA905		
Fiber Length	>80cm		
Threshold Current	----	55mA	95mA
Operating Current	----	220mA	240mA
Operating Voltage	----	7.5V	8.0V
Package Style	Coaxial or B82		


**Coaxial Package View: (Part Number: RWLP-510-020m-4)**



**B82 Package View: (Part Number: RWLP-510-020m-4-B)**



**PIN Bottom View:**



1	LD(+)
2	GND
3	LD(-)

Electrically shorten LD module and store in non-extreme conditions.  
Suggest using the constant current power supply.

